

Lighting Design Lab Qualified LED Fixtures List



This list is maintained by the LDL for Puget Sound Energy, Seattle City Light, Snohomish PUD, Tacoma Power, the Energy Trust of Oregon, Bonneville Power Administration, Idaho Power, and Eugene Water and Electric Board.

NOTE: This is an interim qualifying list while products are being reviewed by ENERGY STAR or DLC.

Products will be permanently removed 12 months after "Post Date".

If you don't see a product on this list, check the ENERGY STAR or DLC lists.

All products carry a warranty of 3 years or more. For questions, please contact ledlist@lightingdesignlab.com.

Fixture/Lamp Type	Manufacturer	Model Number	Lamp Voltage	CCT	Input Wattage	Efficacy LPW	Initial Lumen Output	Rated Lumens	CRI	R9 Value	Post Date
Canopy Luminaires	Deco Lighting	D525-LED-60W	120	5116 K	56.2	94.4	5,306	5,310	67.1	(28.9)	07/21/15
		D530-LED-30W	120	5370 K	29.6	90.0	2,667	2,000	69.9	(12.8)	05/12/15
	Lithonia	VRC LED 1 50K MVOLT	120	5096 K	37.7	93.7	3,529	3,389	78.2	(9.0)	04/03/15
	Noribachi	CAS-021-[optional upgrades]-[mounting]	120	4893 K	31.6	120.0	3,789	3,789	77.4	(3.6)	04/13/15
		CAS-042-[optional upgrades]-[mounting]	120	5017 K	61.5	124.0	7,634	7,634	76.8	(3.9)	04/13/15
Display/Refrigerated Case/Sign Lighting	Deco Lighting	DCH-LED-4-45W	120	3953 K	44.1	102.0	4,531	4,000	82.7	15.1	03/12/15
		DCH-LED-4-60W	120	3953 K	59.1	102.0	6,042	4,000	82.7	15.1	03/12/15
		DSL-LED-4-35-50-UNV	120	5053 K	35.7	124.7	4,453	4,450	82.7	15.1	11/25/15
		DSL-LED-8-60-50-UNV	120	5018 K	63.7	89.8	5,725	5,880	84.5	25.0	11/25/15
	LED Power	CLW-H38J-65K-120D-24V	24	6368 K	6.5	65.0	427	426	84.0	10.3	07/29/15
		CLW-H38V-65K-120D-24V	24	4914 K	6.2	84.0	521	521	83.0	7.3	07/30/15
		RB26LP-6-1/2w-4'-41K-24V	24	4064 K	16.2	80.4	1,299	1,299	83.8	18.3	11/17/15
		RB26LP-6-1/2w-5'-41K-24V	24	4064 K	20.2	80.4	1,624	1,624	83.8	18.3	11/17/15
		RB26LP-6-1/2w-6'-41K-24V	24	4064 K	24.2	80.4	1,948	1,948	83.8	18.3	11/17/15
Fuel Pump Canopy	EnviroLux	ENV-70W-LED-12x12	120	5431 K	66.4	107.7	7,154	7,154	74.5	-	10/15/15
	SNC LED	SNC-CP-100WA1	120	5965 K	101.2	101.5	10,270	10,860	72.5	-	10/14/15
HID Replacements	Deco Lighting	D800-RETRO-120W	120	5662 K	122.5	86.7	10,615	108,080	76.0	(17.8)	06/11/15
		D800-RETRO-140W	120	5662 K	144.7	85.6	12,384	12,374	76.0	(17.8)	06/11/15
		D800-RETRO-160W	120	5662 K	166.8	84.9	14,153	14,081	76.0	(17.8)	06/11/15
		D800-Retro-320W	120	5662 K	322.5	87.8	28,306	28,314	76.0	(17.8)	06/11/15
	Truly Green Solutions	320821	120	5224 K	30.1	129.6	3,900	3,400	83.6	-	01/14/16
High-bay/Low-Bay (including Aisle)	1st Source Lighting	BAY-LHB8-6-S-PO-50K-DAC-U	120	5172 K	296.1	111.0	32,778	32,778	85.0	21.2	12/15/15
	Advanced Energy Ideas	RBL-135W-HO-4-2LC-UNI	120	5340 K	143.2	101.0	14,459	13,600	81.0	9.0	08/06/15
		RBL-135W-HO-4-2LC-UNI	277	5340 K	143.2	101.0	14,459	13,600	81.0	9.0	08/06/15
		RBL-80W-HO-3-2LC-UNI	120	5300 K	87.1	110.4	9,618	8,800	81.0	9.0	08/06/15
		RBL-80W-HO-3-2LC-UNI	277	5300 K	87.1	110.4	9,618	8,800	81.0	9.0	08/06/15
	Beyond Signs Inc dba Beyond LED	102426-4	120	6634 K	21.2	122.5	2,600	2,640	82.7	2.0	12/28/15
	Deco Lighting	DHBX-LED-160	120	5556 K	161.2	95.8	15,440	17,100	70.0	(11.1)	04/13/15
		DHBX-LED-180	120	5556 K	181.2	96.1	14,713	17,100	70.0	(11.1)	04/13/15
		DHBX-LED-360	120	5556 K	361.2	96.4	34,826	34,200	70.0	(11.1)	04/13/15
	EnviroLux	ENV-138W-LED-LHB-PS-UNV	110	5556 K	135.8	139.2	18,909	18,909	71.6	-	08/18/15
		ENV-180W-LED-LHB-PS-UNV (110V)	110	5610 K	191.6	127.7	24,465	24,465	71.4	-	08/18/15
		HE-ENV-138W-LHB-PS-UNV	120	5450 K	131.0	133.5	17,507	17,507	86.0	-	09/15/15
		HE-ENV-180W-LHB-PS-UNV	120	5500 K	198.0	121.9	24,128	24,128	86.0	-	09/15/15
	ESL Vision, LLC	ESL-LBS-14-45W	120	4224 K	43.6	101.9	4,443	4,400	83.0	7.0	07/29/15
	Express Lighting	RLB1050-5500k	120	5222 K	46.7	115.0	5,860	5,830	72.0	-	12/28/15
		RLB2050-5500k	120	5354 K	46.8	108.0	5,830	5,830	72.0	-	12/28/15
	Global Tech	GTSOLM21	120	5650 K	58.3	81.7	4,765	4,765	70.0	-	02/12/13
	KMW, Inc.	NA65-A5709	120	5582 K	71.4	108.2	7,728	6,825	89.1	20.3	04/29/15
NA65-A5709		277	5582 K	68.4	108.2	7,728	6,825	89.1	20.3	04/29/15	
SR40-A40		120	4228 K	43.8	100.2	4,390	4,000	87.0	26.8	04/29/15	

Lighting Design Lab Qualified LED Fixtures List

Fixture/Lamp Type	Manufacturer	Model Number	Lamp Voltage	CCT	Input Wattage	Efficacy LPW	Initial Lumen Output	Rated Lumens	CRI	R9 Value	Post Date
High-bay/Low-Bay (including Aisle)	KMW, Inc.	SR40-A40	277	4228 K	1.0	100.2	4,390	4,000	87.0	26.8	04/29/15
		SR40-A50	120	5111 K	40.4	111.7	4,510	4,000	83.9	21.5	10/19/15
		SR40-A50	277	5111 K	39.6	111.7	4,510	4,000	83.9	21.5	10/19/15
	LDPI Inc.	LE300-P8-V1-(mount)-W-(options)	120	4978 K	81.3	111.0	9,025	9,000	73.6	-	07/23/15
		LE300-P8-V1-(mount)-W-(options)	277	4978 K	81.0	111.0	9,025	9,000	73.6	-	07/23/15
	Maxlite	LSP4805SU44DV35	120	3572 K	39.4	95.8	3,774	3,900	85.3	25.0	06/03/15
		LSP4805SU44DV35	277	3572 K	39.5	95.8	3,774	3,900	85.3	25.0	06/03/15
		LSP9605SU80DV35	120	3581 K	78.2	101.1	7,907	8,013	85.1	24.2	06/03/15
		LSP9605SU80DV35	277	3581 K	78.2	101.1	7,907	8,013	85.1	24.2	06/03/15
	Noribachi	021-CAO-[optional upgrades]-[mounting]	120	4638 K	31.9	104.0	3,306	3,306	74.8	(12.8)	05/27/15
		021-FLL-[optional upgrades]-[mounting]	120	4760 K	31.6	116.0	3,667	3,667	74.5	(15.4)	05/27/15
		140-HBC-[optional upgrades]-[mounting]	120	4735 K	225.8	131.0	29,610	29,610	73.4	(13.6)	05/27/15
		378-FLXXL-[optional upgrades]-[mounting]	277	4765 K	530.0	129.5	70,420	70,420	73.9	(14.4)	08/13/15
HBA-084-[optional upgrades]-[mounting]		120	4869 K	145.9	114.0	16,700	16,700	74.5	(8.2)	04/15/15	
Linear Luminaires (Direct)	Finelite, Inc	HP4-R-X-HO-3500K	277	3500 K	37.7	98.8	3,726	3,726	84.0	14.0	10/15/15
Linear Luminaires (Direct/Indirect)	Deco Lighting	RCTR-LED-4-35W	120	3953 K	34.1	101.0	3,408	3,561	82.7	15.1	02/09/16
		RCTR-LED-4-45W	120	3953 K	45.1	101.0	4,531	4,450	82.7	15.1	02/09/16
		RCTR-LED-4-60W	120	3953 K	58.1	155.5	4,531	5,933	82.7	15.1	02/10/16
Linear Luminaires (Indirect/Direct)	Finelite, Inc	S18 LED-ID-DCO-X-2E-HO-3500K-FTO	277	3523 K	38.1	100.6	3,831	838.75/ft	84.0	14.0	11/25/15
Linear Panels (Troffer)	BJ Take Inc.	BRL-B-4'-4L-840-UNV	120	4000 K	35.5	87.9	3,124	3,100	85.0	19.9	02/09/16
Linear Panels (Troffers)	Kurtzon Lighting	EL-F-2X4-3/LEDH40-120V-HD85	120	4067 K	232.7	85.4	19,870	19,870	84.8	20.3	04/15/15
		EL-G-2X4-3/LEDH40-120V-HD85	120	4067 K	232.7	85.4	19,870	19,870	84.8	20.3	04/15/15
		FP-F-2X4-3/LEDH40-120V-HD85	120	4067 K	232.7	85.4	19,870	19,870	84.8	20.3	04/15/15
		FP-G-2X4-3/LEDH40-120V-HD85	120	4067 K	232.7	85.4	19,870	19,870	84.8	20.3	04/15/15
		KL-F-2X4-3/LEDH40-120V-HD85	120	4067 K	232.7	85.4	19,870	19,870	84.8	20.3	04/15/15
		KL-G-2X4-3/LEDH40-120V-HD85	120	4067 K	232.7	85.4	19,870	19,870	84.8	20.3	04/15/15
		TL-F-2X4-3/LEDH40-120V-HD85	120	4067 K	232.7	85.4	19,870	19,870	84.8	20.3	04/15/15
		TL-G-2X4-3/LEDH40-120V-HD85	120	4067 K	232.7	85.4	19,870	19,870	84.8	20.3	04/15/15
		WL-F-2X4-3/LEDH40-120V-HD85	120	4067 K	232.7	85.4	19,870	19,870	84.8	20.3	04/15/15
		WL-G-2X4-3/LEDH40-120V-HD85	120	4067 K	232.7	85.4	19,870	19,870	84.8	20.3	04/15/15
	Patina Lighting Ltd.	COSMOS – 2x2	120	4052 K	36.3	106.7	3,900	3,900	83.2	8.5	07/29/15
		COSMOS – 2x4 -	120	3927 K	37.2	109.0	4,044	4,000	83.5	10.2	08/18/15
	SAMJIN LND Co., Ltd.	FRK6EA-02535E10US	277	3547 K	25.1	90.6	2,356	2,100	82.8	21.5	02/27/15
FRK6EA-02550E10US		277	5112 K	25.1	94.4	2,432	2,300	86.5	28.5	02/27/15	
Linear Panels (Troffers) retrofit	Deco Lighting	LITHONIA 2PM3N	120	4018 K	35.7	105.0	3,754	3,500	84.5	25.0	03/17/15
	Precision Paragon [P2]	TKD-2X4-VL-F-UL-35K-FRL	120	3599 K	24.6	113.0	2,793	2,793	83.0	24.3	03/16/15
Outdoor Pole/Arm-Mounted Decorative Luminaire	Cyclone Lighting	CG21T4-AGPF-SKY-3-50W-4K	120	4036 K	58.2	65.2	3,749	3,749	73.0	(14.2)	01/14/16
Outdoor Pole-Mounted Area and Roadway Luminaires	Atlas Lighting Products	DD42LED5K	120	5108 K	38.4	99.4	3,813	3,813	72.4	-	12/10/15
	Cree	BXSPA_PPL-U_	120	5483 K	165.1	81.6	13,461	12,744	73.0	(22.0)	02/27/15
	Cyclone Lighting	CG21T4-AGPF-SKY-3-68W-4K	54	4018 K	68.0	77.3	4,236	4,248	74.0	(14.0)	08/13/15
	Deco Lighting	D805-LED 60W	120	5502 K	63.5	72.9	4,623	4,300	68.9	(20.6)	11/20/15
		D805-LED-120W	120	5662 K	126.9	70.7	8,976	9,600	69.4	(17.8)	11/20/15
		D805-LED-200W	120	5662 K	234.2	81.2	19,011	19,000	69.4	(17.8)	11/20/15
		D807-LED 60W	120	5502 K	63.5	72.9	4,623	4,300	68.9	(20.6)	11/20/15
	D807-LED-120W	120	5662 K	126.9	81.2	8,976	9,600	69.4	(17.8)	11/20/15	

Lighting Design Lab Qualified LED Fixtures List

Fixture/Lamp Type	Manufacturer	Model Number	Lamp Voltage	CCT	Input Wattage	Efficacy LPW	Initial Lumen Output	Rated Lumens	CRI	R9 Value	Post Date	
Outdoor Pole-Mounted Area and Roadway Luminaires	Deco Lighting	D807-LED-200W	120	5662 K	234.2	81.2	19,011	9,600	69.4	(17.8)	11/20/15	
		D816-LED-160W	120	5662 K	166.9	84.8	14,153	13,600	76.0	(17.8)	04/29/15	
		DBM-LED-180-50-UNV	120	5114 K	177.2	92.0	18,176	18,100	69.4	(20.2)	12/07/15	
	EnviroLux	ENV-45W-LED-RBF	120	5751 K	49.0	96.5	4,730	4,730	74.5	-	09/14/15	
		ENV-90w-LED-DE-RETKIT-PS	120	5326 K	88.1	120.0	10,566	10,565	71.5	-	07/29/15	
		ENV-90W-LED-LFL	120	5326 K	88.1	120.0	10,565	10,565	71.5	-	09/14/15	
	ESL Vision, LLC	ESL-Bullet-105W	230	4947 K	102.4	80.6	8,258	8,250	71.9	(24.0)	03/13/15	
	Harris Lighting Products	DL140-5000-1	120	5039 K	137.5	94.3	12,903	12,900	84.3	-	05/11/15	
		DL70-5000-1	120	5052 K	67.4	94.3	6,357	6,300	84.4	-	05/11/15	
	KMW, Inc.	SET060-A50	120	5116 K	66.8	109.5	7,319	7,200	80.0	40.1	08/13/15	
		SET060-A50	277	5116 K	66.3	109.5	7,319	7,200	80.0	40.1	08/13/15	
		SET080-A50	120	5185 K	87.5	108.0	9,456	1,000	84.7	43.7	08/13/15	
		SET080-A50	277	5185 K	84.3	108.0	9,456	1,000	84.7	43.7	08/13/15	
		SET100-A50	120	5127 K	104.7	111.4	11,670	12,500	83.8	39.0	08/13/15	
		SET100-A50	277	5127 K	100.2	111.4	11,670	12,500	83.8	39.0	08/13/15	
	LSI Industries	XPTS3 5 LED HO NW UE	120	4136 K	87.6	71.0	6,181	6,200	73.0	-	04/29/15	
	Musco	228 LED	480	5912 K	624.3	104.8	65,446	65,400	74.0	-	07/10/15	
	Neptun Light, Inc.	LED-CRK-180-UNV-841-T3	120	4117 K	180.6	114.7	20,713	18,000	84.8	22.1	11/25/15	
	Noribachi	ALR-105-[optional upgrades]-[mounting]	120	4862 K	173.3	119.0	20,620	20,620	74.0	(17.1)	04/13/15	
		ALR-140-[optional upgrades]-[mounting]	120	4824 K	231.7	113.0	26,170	26,170	74.0	(14.5)	04/29/15	
		CBA-084-[optional upgrades]-[mounting]	120	4878 K	138.9	112.0	15,510	15,510	74.8	(15.3)	04/29/15	
		HBM-140-[optional upgrades]-[mounting]	120	4956 K	226.3	117.0	26,380	26,380	75.2	(8.8)	04/13/15	
		SBL-210-[optional upgrades]-[mounting]	120	4818 K	299.0	117.0	35,120	35,120	74.0	(19.2)	03/20/15	
		SBL-252-[optional upgrades]-[mounting]	120	4858 K	433.3	108.0	56,880	46,880	74.8	(15.5)	04/29/15	
		SBM-140-[optional upgrades]-[mounting]	120	4932 K	231.6	107.0	24,790	24,790	73.8	(17.5)	04/29/15	
	SCHREDER LIGHTING LLC	PIANO 1	120	4268 K	62.9	85.9	5,405	9,000	68.9	(12.3)	03/13/15	
	Outdoor Wall/Ground-Mounted Luminaires	Atlas Lighting Products	WL20LED	120	4602 K	20.1	83.9	1,686	1,685	83.8	-	12/07/15
		Deco Lighting	350096-40W	120	5430 K	38.2	83.1	3,170	3,280	68.9	(18.7)	11/05/15
			D211-LED-90W	120	5662 K	90.8	74.1	6,732	8,000	69.4	(17.8)	06/03/15
			D400-LED-10	120	5430 K	8.2	97.1	792	790	68.9	(18.7)	09/22/15
D400-LED-20			120	5430 K	18.2	83.1	1,584	1,580	68.9	(18.7)	09/22/15	
D400-LED-30			120	5430 K	28.2	83.1	2,376	2,370	68.9	(18.7)	09/22/15	
D404-LED-120W			120	5230 K	117.4	82.8	9,488	9,840	67.0	(26.3)	03/12/15	
D404-LED-80W			120	5230 K	77.4	81.6	6,309	6,560	67.0	(26.3)	03/12/15	
D406-LED-40W			120	5430 K	38.2	83.1	3,170	3,280	68.9	(18.7)	05/28/15	
D406-LED-60W			120	5230 K	57.4	82.8	4,747	4,920	67.0	(26.3)	06/30/15	
D411-LED-10W			120	5430 K	8.2	97.1	792	9	68.9	(18.7)	04/03/15	
D411-LED-15W			120	5430 K	14.2	83.9	1,188	1,230	68.9	(18.7)	04/03/15	
D411-LED-20W			120	5430 K	18.2	83.1	1,584	1,270	68.9	(18.7)	04/03/15	
D415-LED-20W			120	5430 K	18.6	91.1	1,698	1,700	68.9	(18.7)	04/13/15	
D415-LED-30W			120	5430 K	28.6	89.0	2,548	2,550	68.9	(18.7)	04/13/15	
D415-LED-40W			120	5430 K	40.0	84.7	3,388	3,400	68.9	(18.7)	04/13/15	
D454-LED-100-50-UNV-BZ			120	5230 K	99.0	122.4	12,117	12,110	72.0	(26.3)	08/18/15	
D454-LED-90-50-UNV-BZ			120	5230 K	89.0	122.4	10,895	10,895	72.0	(26.3)	09/22/15	
DVTL-LED-10-50-UNV			120	5430 K	10.7	91.4	978	950	68.9	(18.7)	02/10/16	
DVTL-LED-20-50-UNV			120	5315 K	18.2	91.4	1,955	1,900	68.9	(18.7)	02/10/16	
DVTL-LED-30-50-UNV			120	5430 K	32.1	91.4	2,933	2,900	68.9	(18.7)	02/10/16	
VINCI-10W		120	5430 K	10.7	66.9	716	700	68.9	(18.7)	07/21/15		
EnviroLux		ENV-180W-LED-LFL-PS-UNV	120	5818 K	174.0	114.2	19,871	19,871	74.5	-	08/18/15	
		ENV-45W-LED-HFMWP	120	5774 K	49.9	100.4	5,008	5,008	74.1	-	09/15/15	
		ENV-45W-LED-LWP	120	5467 K	49.6	101.8	5,051	5,051	74.3	-	09/14/15	
		ENV-45W-LED-LWPCO	120	5370 K	49.3	113.9	5,616	5,616	72.5	-	09/15/15	

Lighting Design Lab Qualified LED Fixtures List

Fixture/Lamp Type	Manufacturer	Model Number	Lamp Voltage	CCT	Input Wattage	Efficacy LPW	Initial Lumen Output	Rated Lumens	CRI	R9 Value	Post Date	
Outdoor Wall/Ground-Mounted Luminaires	EnviroLux	ENV-70W-LED-LWP	277	5560 K	63.5	100.2	6,453	6,453	74.3	-	09/14/15	
		ENV-70W-LED-LWPCO	120	5450 K	65.2	109.5	7,142	7,142	72.5	-	09/14/15	
		ENV-90W-LED-Slimline Wallpack	120	5480 K	87.1	90.9	7,916	7,916	74.2	-	09/14/15	
	ESL Vision, LLC		ESL-FLS-100W-350	120	5208 K	98.4	106.0	10,455	1,000	85.5	23.0	12/24/15
	Howard Lighting Products		MLWP-5033-MV-XXX	120	5034 K	32.1	69.7	2,238	2,240	72.5	-	02/24/15
			MLWP-5046-MV-XXX	120	5004 K	46.2	74.7	3,449	3,450	82.0	-	02/24/15
			MLWP-5070-MV-XXX	120	5216 K	70.2	72.0	5,055	5,060	72.8	-	02/24/15
	Hubbell Lighting		WGH-110L-4K-U-M	120	4013 K	54.0	96.7	5,219	4,888	82.0	12.1	11/18/15
			WGH-110L-4K-U-M	277	4013 K	54.0	96.7	5,219	4,888	82.0	12.1	11/18/15
	KMW, Inc.		WP050-A50	120	5157 K	52.1	118.0	6,147	6,250	84.0	24.0	10/19/15
			WP050-A50	277	5157 K	51.9	118.0	6,147	6,250	84.0	24.0	10/19/15
	Lithonia		TWH LED 20C 50K	120	5062 K	72.6	77.8	5,654	5,562	67.5	(30.5)	03/03/15
	Maxlite		MLLWP60LED50	120	4728 K	51.3	88.3	4,525	4,030	83.1	13.0	05/11/15
			MLLWP60LED50	277	4728 K	50.6	88.3	4,525	4,030	83.1	13.0	05/11/15
			MLSWP30LED50	120	4850 K	29.2	74.1	2,166	2,165	83.6	17.0	05/11/15
			SECA15U50BPC12	120	5173 K	15.1	91.0	1,364	1,450	83.3	-	02/09/16
			SECA15U50BPC12	277	5173 K	15.6	91.0	1,364	1,450	83.3	-	02/09/16
	Noribachi		Hex-042-[optional upgrades]-[mounting]	120	4777 K	61.0	113.0	6,880	6,880	74.3	(16.5)	04/15/15
			SBM-084-[optional upgrades]-[mounting]	120	4834 K	139.7	119.0	16,580	16,580	74.2	(16.8)	04/15/15
			WPF-063-[optional upgrades]-[mounting]	120	4827 K	94.6	120.0	11,320	11,320	73.7	(19.9)	04/03/15
	RAB Lighting		WP1LED30	120	5200 K	31.4	97.5	3,060	3,060	83.0	-	09/11/15
		WP2LED24	120	5018 K	24.4	120.6	2,942	2,942	81.0	-	09/04/15	
		WP2LED37	120	5094 K	38.7	111.9	4,329	4,329	82.0	-	09/11/15	
		WP3LED55	120	5066 K	56.7	117.2	6,645	6,645	81.0	-	09/04/15	
Parking Garage/Canopy Fixtures	ALP Lighting Components	F2402RLED-21B3	120	4233 K	51.7	108.4	5,602	5,602	83.5	-	01/06/16	
	Deco Lighting	D206-LED-100	120	5662 K	100.9	74.1	7,480	8,000	69.4	(17.8)	04/14/15	
		D206-LED-120	120	5662 K	126.9	70.7	8,976	9,600	69.4	(17.8)	04/14/15	
		D206-LED-150	120	5662 K	150.9	74.4	11,219	12,000	69.4	(17.8)	04/14/15	
	EnviroLux		ENV-45W-LED-12x12	120	5368 K	49.0	111.6	5,470	5,470	74.4	-	09/14/15
			ENV-45W-LED-Garage	120	5787 K	49.6	109.2	5,417	5,417	76.0	-	09/14/15
			ENV-45W-LED-SE-RETKIT-PS-UNV	120	5537 K	65.0	99.5	6,472	6,472	85.8	-	09/14/15
			ENV-70W-LED-Garage	120	5921 K	65.1	105.3	6,858	6,858	76.2	-	09/15/15
			ENV-90W-LED-18x18-Canopy	277	5695 K	87.7	112.9	9,924	9,924	74.7	-	09/14/15
	Lithonia Lighting		FEM4 LED 3L IMACD	120	4087 K	38.5	88.8	3,418	3,418	67.2	-	11/05/15
	Maxlite		CAN20U50B	120	5105 K	20.9	118.6	2,475	2,475	73.9	(16.0)	11/18/15
		CAN20U50B	277	5105 K	21.4	115.6	2,467	2,475	73.9	(16.0)	11/18/15	
		LSP4805HU44DV50PKG	120	5295 K	39.1	129.5	5,063	4,106	83.7	13.2	02/20/15	
Recessed, Surface and Pendant-Mounted Downlights	Aquarii, Inc.	AX-150-30-80-36	120	3017 K	148.5	74.4	11,051	12,000	79.3	(2.4)	07/08/15	
	CGF Design	E74-OP-LED80-CT4-GEN3-UNV-0-10D-WH	305	5210 K	76.3	88.8	6,772	8,840	85.0	21.0	04/03/15	
	H.E. Williams	17-4-L55/840-A-DIM-UNV	120	4000 K	49.1	113.8	5,591	5,500	82.0	18.6	07/14/15	
		18-4-L90/840-A-DIM-UNV	120	4000 K	81.4	111.7	9,088	9,000	82.0	20.4	07/14/15	
	Luminaire LED, Inc.	ARV13-25WHP-4100K-120-277-OP-WHT	120	4310 K	25.9	92.1	2,385	2,385	87.0	-	05/11/15	
		ARV13-25WHP-4100K-120-277-OP-WHT	277	4310 K	25.7	92.1	2,385	2,385	87.0	-	05/11/15	
	Luminis		AR148-L1W30	120	4135 K	32.9	98.7	3,248	3,248	81.0	-	06/11/15
Stairwell and passageway	Maxlite	MLVPC14LED50CP	120	5234 K	13.4	83.6	1,123	11	65.5	-	02/25/16	
		MLVPC14LED50CP	277	5234 K	14.1	83.6	1,123	11	65.5	-	02/25/16	
		MLVPW14LED50CP	120	5234 K	13.4	83.6	1,123	11	65.5	-	02/25/16	
		MLVPW14LED50CP	277	5234 K	14.1	83.6	1,123	11	65.5	-	02/25/16	
Wall Wash Luminaires	ARVA, LLC	HL-XPL-2-30W	120	2984 K	29.7	85.8	2,547	2,750	83.8	23.0	04/15/15	

Lighting Design Lab Qualified LED Fixtures List

Fixture/Lamp Type	Manufacturer	Model Number	Lamp Voltage	CCT	Input Wattage	Efficacy LPW	Initial Lumen Output	Rated Lumens	CRI	R9 Value	Post Date
Wall Wash Luminaires	ARVA, LLC	HL-XPL-4-70W	120	3114 K	68.9	82.5	5,634	6,100	83.1	19.0	04/15/15
Wall Wash Luminaires (sconce)	v2 Lighting Group, Inc	VC3S-xx-13804060-xx	120	3972 K	19.4	59.0	1,155	1,300	83.0	21.8	04/13/15